

REMARKS:

The present Amendment makes changes in the title, drawings, specification and claims, and adds an Abstract, to conform the present PCT application to the requirements of United States patent practice. The
5 cancellation of claims 1-16 in favor of the claims presented herein has been made solely because the amount of strikethroughs and underlining in claims 1-16 that would have been necessary to confirm those claims to the requirements of United States patent practice would have been unduly burdensome and confusing. No difference in the claim language between
10 claims 1-16 and the claims presented herein has been made for the purpose of distinguishing any of the claims presented herein over the teachings of the prior art of record. Accordingly, no difference in the claim language between claims 1-16 and the claims presented herein is considered by the Applicant to constitute a surrender of any of the subject matter encompassed within the
15 scope of claims 1-16.

Early consideration of the application on the merits is respectfully requested.

Submitted by,

Steven H. Noll

(Reg. 28,982)

Schiff, Hardin LLP

CUSTOMER NO. 26574

Patent Department

6600 Sears Tower

233 South Wacker Drive

Chicago, Illinois 60606

Telephone: 312/258-5790

Attorneys for Applicant.

MARKED-UP COPY

[~~New motion sensor~~

Technical field

SPECIFICATIONTITLE

5 **"MOTION SENSOR CONTAINING FLUID INCORPORATING MOLECULES
EXHIBITING MOTION-DEPENDENT ANISOTROPIC PROPERTIES"**

BACKGROUND OF THE INVENTION

Field of the Invention

10 The invention concerns a motion sensor for measuring a patient's activity level of the type having ~~comprising~~ a fluid-tight, biocompatible housing, a ~~plurality~~ number of electrodes ~~being~~ coupled to the housing and the housing ~~comprising~~ containing a fluid. Furthermore, the invention relates to an implantable cardiac pacemaker ~~comprising the~~ incorporating such a motion sensor.

Prior art

15 **Description of the Prior Art**

20 Pacemakers are used to pace the beating frequency of the heart. They have been of greatest importance for helping individuals suffering from various heart diseases and/or failures to live rather normal lives. Pacemakers function by generating electrical pulses, which stimulate the heart. In order to pace the heart in a correct way, the specific pulse pattern of the individual heart must be known. External It is advantageous to detect external parameters, such as the motion of the patient, ~~are advantageously known~~, in order for the pacemaker to stimulate the heart as correctly as possible.

25 Normally, the motion of the patient is measured by some kind of motion sensor, which ~~sensor~~ is connected to the pacemaker. ~~US-A-5755741~~ United States Patent No. 5,755,741 discloses an implantable sensor providing an indication of movement and orientation of a patient. The sensor may be connected to a pacemaker. The sensor ~~comprises~~ has a cylindrical enclosure

MARKED-UP COPY

having a central electrode within a cavity of the enclosure, and one or more peripheral electrodes within the cavity. An electrolytic fluid is positioned in the enclosure so that movement of the sensor results in variations of the amount of the fluid between the central electrode and one or more of the peripheral electrodes. An alternating current applied to the electrodes will ~~render a~~ produce
5 an output voltage signal, which varies in accordance with the movements of the fluid (and the sensor).

~~US-A-5833713~~ United States Patent No. 5,833,713 discloses an accelerometer-based, multi-axis physical activity sensor for use with a rate-
10 responsive pacemaker. A piezoelectric polymer film is adhered to the surface of an electrically conductive substrate on the sensor. In response to bodily accelerations the piezoelectric film produces an output signal.

~~US-A-5233984~~ United States Patent No. 5,233,984 discloses a multi-axis sensor, for example connected to a pacemaker, for measuring a patient's activity
15 level. The sensor ~~comprises~~ has a hermetically sealed, fluid-tight, biocompatible housing, ~~whereby a plurality~~ with a number of electrodes is coupled to the sides of the housing, and a central electrode is positioned within the housing. An electrically conductive electrolyte fills about half of the housing, allowing voltage changes, due to motion of the sensor, between the central electrode and the other
20 electrodes to be monitored.

Also, ~~US-A-4869251~~ United States Patent No. 4,869,251 discloses a pacemaker having a sensor for detecting inertial and/or rotational movements of a patient. The sensor has a hollow member, with at least one freely moveable member therein generating a mechanical vibration upon movement of the patient.
25 A transducer generates an electric signal corresponding to the mechanical vibrations. It is stated that the hollow member may be filled with a fluid and/or a ~~plurality~~ number of particles producing pressure to the walls of the hollow member. It is also stated that the sensitivity of the sensor may be different in different directions. For example, the moveable element may be a magnetic
30 dipole, and the transducer may be one or more coils arranged around the hollow

MARKED-UP COPY

member, whereby a current is generated in the coils when the moveable element changes position in the interior of the hollow member. Depending on configuration, however, the mobility of the movable element may ~~however~~ degrade due to mechanical wear.

5 Accordingly, ~~the~~ Such known motion sensors ~~of the prior art normally~~
generally rely on moving mechanical components, and therefore they may be
difficult to miniaturise miniaturize further. This is a problem, ~~since~~ because the
size of the motion sensor (and pacemakers) advantageously is as small as
possible, in order to disturb the biological system into which they are put
10 implanted as little as possible. Furthermore, as mentioned above, mechanically
based sensors may suffer from mechanical wear, which can lead to their failure.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a motion
sensor, ~~which~~ that overcomes the drawbacks of the prior art, and ~~thereby~~
15 comprises has as few mechanical parts as possible, as well as the sensor ~~further~~
being as small as possible, and relying on a technical principle making it as
resistant to failure as possible.

Summary of the invention

These and other objects are accomplished by a motion sensor according to
20 ~~claim 1 of~~ the present invention, which relies on the principle of an electrically
detectable anisotropic fluid, which fluid orients itself in relation to external motion.

~~Hereby, a~~ A sensor thus is ~~provided in which~~ achieved employing no
moving parts ~~are comprised~~, and which therefore ~~is possible to make~~ can be
made very small.

25 In a preferred embodiment, the anisotropic fluid ~~comprises~~ contains long,
rigid LCP-molecules, on which electrically detectable magnetic nanoparticles are
covalently linked.

MARKED-UP COPY

In another embodiment a magnetic field is applied to the anisotropic fluid, and the alignment of the anisotropic molecules is detected by measuring the capacitance of the fluid.

5 In yet another embodiment an electrostatic field is applied to the anisotropic fluid, and the alignment of the anisotropic molecules is detected by measuring the capacitance of the fluid.

Moreover, the invention relates to an electrically detectable anisotropic fluid comprising a liquid crystalline polymer (LCP) as the anisotropic fluid, which LCP is covalently bound to an iron-oxide nanoparticle. This fluid is specifically suitable
10 for use in the motion sensor of the invention.

Furthermore, the invention relates to an implantable pacemaker ~~comprising~~ incorporating the motion sensor of the invention. ~~Hereby, a patients~~ A patient's heart is paced as a response to the ~~patients~~ patient's motion, as sensed by the motion sensor of the invention.

15 Accordingly, the drawbacks of the prior art are overcome.

Short description of the drawings

DESCRIPTION OF THE DRAWINGS

Figure 1 ~~shows a principal sketch~~ is a block diagram of a motion sensor according to one embodiment of the invention.

20 Figure 2 ~~shows a principal sketch~~ is a block diagram of a rate response pacemaker accordingly to the present invention, incorporating a motion sensor according to the present invention.

Figure 3 shows a zwitterion.

25 Figure 4 ~~shows a principal sketch~~ is a block diagram of a motion sensor according to another embodiment of the invention.

Preferred embodiments

MARKED-UP COPY

DESCRIPTION OF THE PREFERRED EMBODIMENTS

~~The idea~~ An aim of the invention is to provide a motion sensor, especially adapted for use with a pacemaker, which is as small as possible, and which circumvents the problem of mechanical wear in a sensor comprising several
5 mechanical parts. This is ~~provided~~ accomplished by a sensor, ~~which that~~ relies on the principle of an anisotropic fluid or an anisotropic molecule within a fluid. ~~Thereby~~ Thus, the only moving parts of the sensor are fluids.

~~Accordingly, in a first aspect the invention relates to~~ In accordance with the invention a motion sensor for measuring a patient's activity level ~~comprising~~ has a
10 fluid-tight, ~~bio-compatible~~ biocompatible housing, a ~~plurality~~ number of electrodes ~~being~~ coupled to the housing, and the housing ~~comprising~~ contains a fluid that ~~comprises~~ includes at least one anisotropic molecule, the anisotropic properties of which ~~are changed~~ change in relation to the motion of the fluid, ~~whereby~~ so the state of the anisotropic molecules of the fluid is detectable by the electrodes.

15 In a preferred embodiment, the motion sensor is implantable in the a patient ~~in question~~. ~~However, the~~ The motion sensor alternatively may also be adapted for external use, i.e. not being implanted in the body of the patient, but communicating ~~by for example some telemetric means~~ with an implanted pacemaker, such as by telemetry.

20 ~~By a~~ The term "patient" is ~~in the context of the invention meant~~ as used herein means an animal, especially a human, ~~which is~~ in need of a motion sensor. This may ~~for example include~~, for example, persons ~~which have~~ having a pacemaker or ~~whom is~~ who are to be equipped with a pacemaker. ~~However, the~~ The motion sensor of the invention, however, need ~~must~~ not necessarily be
25 coupled to a pacemaker, but may also be connected to any other device or circuitry for which the output of the motion sensor is relevant.

By As used herein, a patient's "activity level" is ~~meant~~ means the degree of motion for the specific patient. For example, for a pacemaker to deliver the correct pulses to a patients heart, it is important to correlate these pulses with the

MARKED-UP COPY

"activity level" of the patient, in order for the pacing pulses and the resulting heart responses to be suited for the patients present need. Thus, it is preferred that the paced heart rate is adaptable to different levels of exertion by the patient.

By As used herein, "a plurality number of electrodes " ~~is meant~~ means at least one electrode pair, having the capacity to monitor at least one electronic parameter.

An anisotropic molecule will orient itself in relation to ~~the motional stress~~ motion-caused forces to which it is subjected to. Thus, for example, an anisotropic molecule may exhibit anisotropic properties at rest and isotropic properties when agitated (i.e. different states). Accordingly, a plurality number of molecules of this kind will, like a crystal, align in a common direction at rest, or in a laminar shearing force. The viscosity, as well as several other physico-chemical properties, such as optical transmission, heat transfer, polarity, conductivity etc., will then be very different in the alignment direction compared to other directions, especially the perpendicular direction. However, if agitated, the molecular alignments will become random ~~randomised~~, and as a result properties such as viscosity or dielectric constant will be practically equal in all directions. Thus, when a patient carrying the sensor of the invention moves, the sensor will sense these movements (or lack of movements) and create an output signal, ~~which is~~ based dependent on the movements them.

Liquid crystalline polymers (LCP's)(Langmuir 2001, 17, 2900-2906) are fluids having anisotropic properties at rest and isotropic properties during agitation. LCP's, in the context of the invention, are long rigid molecules, which have an aspect-ratio (length/diameter) of greater than about (10/1). One example, which is suitable for the purposes of the invention, is poly-(p-phenylene) with a degree of ~~polymerisation~~ polymerization (n) equal to or greater than 10. In this context, the aspect-ratio would be a more relevant term than for example molecule length, since a rigid rod polymer with a wide diameter will not exhibit anisotropic properties at the same length or degree of ~~polymerisation~~ polymerization as a rigid rod polymer with a narrow diameter. The aspect-ratio,

MARKED-UP COPY

however, provides a good way to measure the intrinsic anisotropy of the polymer molecules.

Thus, according to one embodiment of the invention the anisotropic molecule is a liquid crystalline polymer (LCP).

5 Some other examples of liquid crystalline polymers suitable for the invention are given below. However, this list is not exhaustive, and other compounds may also be used.

 A copolymer of p-hydroxybenzoic acid and polyethylene terephthalate. (Japanese Patent Publication No. 18016/1981); a copolymer of p-hydroxybenzoic
10 acid, polyethylene terephthalate, aromatic diol (such as 4,4'-dihydroxybiphenyl), and aromatic dicarboxylic acid, with improved flowability and heat resistance. (Japanese Patent Laid-open No. 30523/1988); a copolymer of p-hydroxybenzoic acid, 4,4'-dihydroxybiphenyl, t-butylhydroquinone, and terephthalic acid. (Japanese Patent Laid-open No. 164719/1987); a copolymer of p-hydroxybenzoic
15 acid, 4,4'- dihydroxybiphenyl, isophthalic acid, and terephthalic acid. (Japanese Patent Publication No. 24407/1982 and Japanese Patent Laid-open No. 25046/1985); a copolymer of p-hydroxybenzoic acid and 6-hydroxy-2-naphthoic acid. (Japanese Patent Laid-open No. 77691/1979); copolyesters of terephthalic acid, alkylhydroquinone, p-hydroxybenzoic acid and poly(alkylene terephthalate),
20 the alkylene substituent preferably ~~comprising~~ containing ethylene or butylene and the alkyl substituent of the hydroquinone preferably ~~comprising~~ containing a lower alkyl group such as propyl or (tertiary) butyl; copolyesters of p-hydroxybenzoic acid and poly(alkylene terephthalate), the alkylene group preferably being ethylene or butylene; copolyesters of terephthalic acid, alkylhydroquinone, p-
25 hydroxybenzoic acid and hydroxyalkylphenyl-alkanoic acids, the alkyl-substituent of the hydroquinone preferably ~~comprising~~ containing a lower alkyl group such as propyl or (tertiary) butyl, the alkanoic acid preferably containing 3 to 8 carbon atoms, propanoic acid being particularly preferred, and blockcopolyesters of trimellithic imide-terminated poly(THF) or polysilicone, containing the imide group
30 in para- or meta-position i.e. N-(4-carboxy-phenyl)-trimellit imide or N-(3'-acetoxy-

MARKED-UP COPY

phenyl)-trimellit imide, with acetoxybenzoic acid and at least one repeating unit selected from the group ~~comprising~~ including diacetoxy diphenyl, hydroquinone diacetate, terephthalic acid, a trimer designated HBA--HQ--HBA (the synthesis of which is described in Europ. Polym. J. 20, 3, 225-235 (1984), and poly(ethylene terephthalate) (PET).

The molecular weight of the liquid crystal polymer used in the present invention depends on the character of the repeating units of the LCP. Usually, the molecular weight is in the range of about 1,000 to 300,000. If fully aromatic polyesters are used as LCP's, their molecular weight is typically in the range of about 2,000 to 200,000, preferably about 10,000 to 50,000.

More general details on liquid crystalline polymers and their properties and applications are given in an article titled "Liquid Crystal Polymers and Their Applications" by Chung et al. in Handbook of Polymer Science and Technology, Vol. 2 (1989) 625-675.

In order to be able to detect the anisotropic properties ~~one may for example attach a doping agent, for example, may be attached~~ to the anisotropic molecule, ~~which the~~ doping agent ~~have~~ having the capacity to provide a readable electronic signal. Thus, the doping agent constitutes an electrically detectable ~~part. Hereby,~~ component allowing a patient's activity level is possible to be monitored ~~monitor~~.

The doping agent is coupled to the LCP-molecule by any common chemical bonding technique. Preferably, the doping agent is coupled to the LCP-molecule by covalent bonding. ~~The~~ Those skilled ~~person~~ in the art easily ~~recognises~~ are familiar with techniques for binding the doping agent to the LCP, e.g. by hydrosilylation reactions using organosilane intermediates, for example dimethylvinyl silane.

Therefore, according to another embodiment the anisotropic molecule ~~comprises~~ includes an electrically detectable component ~~part~~.

MARKED-UP COPY

The production of silica-coated iron oxide nanoparticles is described in the reference article Langmuir, Vol 17, No. 10, 2001 (2900-2906). Basically, they are produced in solution from appropriate chemical reagents, aided by suspension in organic surfactants. The particles are treated with tetraethylorthosilicate (TEOS) to form a silica coating. These particles are magnetic, and can be bound to an isotropic (rigid rod) molecule using covalent bonding and standard silica surface treatment chemistry, for example by silanization with dimethylvinyl silane. In one embodiment of the present invention, the silane group bonds to the silica surface, and the vinyl group can form a covalent bond with many different kinds of organic molecules, including Liquid Crystalline Polymers (LCP's) containing dipoles. Under a small magnetic field (B), such as greater than about 0.5 Gauss, a preferential orientation will be induced, so that the magnetic particles line up in the magnetic field. The degree of alignment is preferably detected by measurement of capacitance across the fluid. The tendency for alignment is dependent on agitation because the dipoles will be forced by the magnetic particles to line up in the preferential orientation, but that orientation is disturbed by fluid motion.

For a principal sketch of one embodiment of the motion sensor of the invention see figure 1. The sensor 10 comprises a housing 11, which is filled by a fluid. The fluid comprises at least partly anisotropic molecules of the invention. Furthermore, a magnetic field is generated by the magnets 14 and 15. A capacitor 12 and 13 measures the capacitance of the fluid, and thus a variation in the anisotropic status of the fluid is monitored.

Examples of doping agents are ions or molecular dipoles. Preferably, a magnetically aligned nanoparticle (Langmuir 2001, 17, 2900-2906), or a charge-separated ion-pair, such as a zwitterionic pair (positive charge at one end, negative at the other) is used. The nanoparticle is in a preferred embodiment an iron-oxide nanoparticle, wherein iron-oxide may be represented by e.g. Fe_3O_4 , or $\gamma\text{-Fe}_2\text{O}_3$ (Langmuir 2001, 17, 2900-2906)

MARKED-UP COPY

Thus, in yet another embodiment of the invention the detectable part is a magnetic nanoparticle, a zwitterionic pair or a charge separated ion-pair, preferably a magnetic iron-oxide nanoparticle.

5 In one preferred embodiment, the anisotropic fluid comprises long rigid LCP-molecules, on which electrically detectable charge-separated separated ion pairs are covalently linked.

In another embodiment an electric field is applied to the anisotropic fluid, and alignment of the anisotropic molecules is detected by measuring the capacitance of the fluid.

10 Moreover, the invention relates to an electrically detectable anisotropic fluid comprising a LCP as the anisotropic fluid, which LCP is covalently bound to two charge-separated separated ion pairs of different charge at each end of the LCP rigid rod.

15 In a non-polar medium such as an LCP fluid, ions are associated with other ions of opposite charge, forming an ion pair. One ion pair alone is sufficient to cause orientation in an electric field. However, a very strong field would be required to align long rod LCPs if only one ion pair were attached at one end. Consequently, it is preferable to have two different ion pairs at each end (one must be a negative group covalently bond, such as a carboxylate ion $R-COO^-$ with counter-ion Na^+ , and the other a positive ionic group such as $R'-NH_3^+$ with counter-ion Cl^-). Choices of the covalently bonded ion and its counter-ion are many, and any choice that is suitable for use in the present invention may be chosen. A "zwitterion" is the name for any molecule containing two such ionic groups of opposite charge as described above and illustrated in figure 3.

25 In an electrostatic field, such as created between capacitor plates of opposite charge (figure 4), the charges on the LCP pictured above will cause the rigid rod to readily align itself in the field, creating anisotropy behavior in the many properties of the fluid, including (but not limited to) viscosity, resistance, dielectric constant, etc. A very low electrical field strength (E) may be possible to facilitate

MARKED-UP COPY

the ~~alignement~~ alignment, preferably E less than 1 V/m. Agitation of the fluid causes temporary ~~randomisation~~ randomization of orientation which is easily detected in a number of ways as discussed previously for the magnetic particle doped materials. At rest, the anisotropy is restored to the fluid due to the influence of the electrical field aligning the ion pairs of these zwitterionic molecules. The viscosity, as well as other physico-chemical properties, such as optical transmission, heat transfer, polarity, conductivity, etc., will then be different in the alignment direction compared to other directions, especially the perpendicular direction.

10 Figure 4 illustrates this embodiment. A motion sensor 40 comprises a ~~bio-compatible~~ biocompatible housing 41 and electrodes 42 and 43. Positively and negatively ~~charged~~ charged capacitor plates, 44 and 45, respectively, are used to align the LCP-molecules in the housing.

15 ~~A person~~ Those skilled in the art (of combinatorial organic chemistry, for example) ~~easily recognizes~~ are familiar with techniques for binding the doping agent to the LCP, e.g, by hydrosilylation reactions involving organosilane intermediates, for example dimethylvinylsilane, which leaves a vinyl group for binding e.g. organic acid and base groups such as $-R-COO^-$ and $-R'-NH_3^+$ where R and R' are any organic moiety containing a vinyl group.

20 ~~An purpose with~~ A reason for the use of a zwitterionic or charge-separated ion pair as a dopant on the LCP-molecule, and the use of an electrostatic field (such as between capacitor plates) for alignment of the LCP-molecules, is that it is desirable to avoid disturbances of the ~~function~~ function of a pacemaker from external magnetic fields, and this need is thus met by this embodiment.

25 ~~Hereby, the~~ The electrical/magnetic signature is representative of the degree of alignment of the LCP's LCPs. As a consequence, the amount of agitation (i.e. patient activity) is correlated to the electrical or magnetic signal, which the sensor and/or pacemaker circuitry is designed to detect. As a result a motion sensor having no moving parts (except the anisotropic fluid) and that can

MARKED-UP COPY

be made very small can be manufactured. For example, the sensor may have a cavity volume of a few mm^3 or less, such as less than 10 mm^3 , preferably less than 5 mm^3 , most preferably less than 1 mm^3 .

5 The suitable electronic signal to be monitored may vary depending on the nature of the system and its chemical content. However, for many applications measure of capacitance is suitable. In other cases measurement of voltage, voltage changes, impedance or resistance may be suitable.

Thus, in ~~still~~ another embodiment the state of the anisotropic molecule is monitored by measuring the capacitance in the fluid.

10 In ~~yet~~ another embodiment the state of the anisotropic molecule is monitored by measuring the resistance in the fluid.

In ~~yet~~ another embodiment, coils are arranged around the housing. Upon a variation in the state of the anisotropic fluid, a voltage is induced in the coils, which voltage is used as a signal. For example, the coil may be of insulated
15 silver/copper wire.

The nanoparticulate size of the anisotropic entity molecules enables low enough viscosity that no moving parts (other than fluid) is necessary, even in small devices like a pacemaker. A half-empty cylinder is one preferred example of the container. This container preferably has a magnetic N and a magnetic S
20 pole provided by placement of permanent magnets 14 and 15 on opposite sides of its diameter. The electric sensor (e.g. capacitor electrodes 12 and 13) may also be on opposite sides of the cylinder diameter, though preferably normal (90 degrees) to the magnetic diameter (see ~~figure~~ Figure 1).

It is not required to have the capacitor electrodes normal to the magnetic
25 field, but it provides the optimum signal output. Each molecule of the fluid will act as a dipole with a dipole moment in a particular direction. When in a magnetic field, the dipole moments will tend to align in due to being bound to the magnetic particles as described in the reference article. The net dipole moment of the fluid

MARKED-UP COPY

is then finite and detectable as capacitance between the capacitance electrode. This "high order state" is detectable across any plane of the fluid except that parallel to the magnetic field, since in the parallel plane the LCP molecule ends face the electrodes and the LCP fluid would appear to the sensor to be small molecules with no preferable orientation in that plane. Therefore, in the "high order state", the signal is obtained as long as the capacitor electrodes are not in the parallel plane, a detectable signal in any other plane, and an optimum signal is obtained in the perpendicular plane. Note that when agitated, the dipoles become randomly oriented yielding a much lower net dipole moment - this "low order state" gives the same signal output independent of orientation between the capacitor electrodes and the magnetic field. So to achieve the maximum difference between the "at rest" state (high order) and the active state (low order), perpendicular is the preferred set-up, but sensitive electronics means that any orientation other than parallel to the magnetic field suffices.

However, in yet another embodiment ~~the invention refers to an anisotropic molecule showing~~ exhibiting a specific dipole moment even in the parallel plane is used.

In the invention, air is preferably used as the agitating medium. However, it is also possible to have a completely filled cavity if it is ensured that the anisotropic fluid is agitated with body motion (note, it is fluid agitation that results in its altered properties). One such embodiment is a flexible housing completely filled, whereby the motion of the housing provides the agitation. Another embodiment would be to have a completely filled cavity containing inert particles in the fluid, which agitate the fluid with body motion (kind of like the ball bearing in spray-paint cans). If air is the agitator (which is preferred), 98% fluid is a reasonable upper limit. As a lower limit, enough fluid to fill out the space between electrodes (preferably capacitor plates) is needed, which would necessitate a lower limit of about 20% fluid.

It is important that the sensor is be implantable in the human body. ~~For this to be readily made, so~~ the sensor is preferably constructed of ~~bio-compatible~~

MARKED-UP COPY

biocompatible material. Furthermore, since the housing of the sensor ~~comprises~~ contains a fluid, it is important that the housing is be entirely fluid-tight, in order to ~~secure~~ assure the function of the sensor as well as ~~the well-being~~ no risk of harm of the patient.

5 The housing may be formed, for example, ~~consist~~ of glass, ceramic, plexiglass Plexiglas®, thermoplastic, curable plastic, metal, rubber (for example silicone rubber) or any other suitable material. Also, the housing may be formed of any conventional structural biocompatible dielectric material, such as ceramic, phenolic resin, epoxy resin or polysulfone. The shape of the housing may for
10 example be spherical, cylindrical, cubical, of a horseshoe-shaped annulus form, or any other functional shape.

 In one embodiment, the housing is configured in the shape of a cube having six sides, and the electrode includes six generally identical rectangularly shaped side electrodes. Each of these side electrodes is coupled to one side of
15 the housing. The electrodes are electrically accessible outside of the sensor via conventional feed-throughs.

 The electrodes can assume different shapes, such as a rectangle, a circle, a triangle, a parabola, or such other geometric shapes that will enable the mapping of the voltages, voltage changes, impedances and impedance changes
20 between various reference points on the side electrodes.

 These side electrodes are composed of conventional conductive material such as stainless steel or titanium. The side electrodes may be supported remotely by feed-through connector wires or may be connected to the side via an insulator.

25 In ~~still~~ another embodiment ~~the housing comprises means for creating shear forces acting on~~ in the anisotropic fluid are produced by using a solid mechanical moveable element, such as a bead or a ball made of non-ferromagnetic metal, contained in the housing.

MARKED-UP COPY

The sensitivity of the sensor can be varied by varying the concentration of the anisotropic molecule in the fluid.

The sensitivity of the sensor may also be varied by varying the viscosity of the fluid in the housing.

5 ~~In a second aspect, the~~ The invention refers to also encompasses an electrically detectable anisotropic fluid ~~comprising~~ containing a liquid crystalline polymer (LCP) as the anisotropic fluid, which LCP is covalently bound to an iron-oxide nanoparticle. ~~Hereby~~ Thus, a fluid is provided ~~which~~ that is specifically adapted for use in a motion sensor of the invention.

10 ~~In a third aspect, the~~ The invention relates to also encompasses an implantable cardiac pacemaker ~~comprising~~ incorporating the implantable motion sensor described above, and means for pacing a heart, such as a pulse generator, as a response to the activity level as detected by the motion sensor, which means is connected to said motion sensor. The physical activity of the
15 patient in which the pacemaker is implanted is monitored using the sensor, and the output signal of the sensor is used to control the frequency of the pulse generator.

In an alternative embodiment of this aspect, the pacemaker does not
20 ~~comprise~~ contain the motion sensor itself ~~of the invention~~, but means contains a unit for receiving signals from an external motion sensor. In this case, the external motion sensor communicates by means of telemetry or the like with the pacemaker.

By As used herein "implantable pacemaker" ~~is meant that the~~ means a pacemaker ~~in question must be possible to implant~~ that can be safely implanted in
25 a patient, and thus the pacemaker should be constructed of ~~for example~~ biocompatible material.

By The term "means for pacing a heart" ~~is meant~~ means any kind of conventional pacemaker or pulse generator, such as implantable cardiac

MARKED-UP COPY

defibrillators, such as Microny® or Regency®. ~~The~~ Those skilled ~~person~~ in the art would know suitable devices for use for this purpose.

In one embodiment, the sensor forms an entirely self-contained system within the heart pacemaker, which requires no additional external detectors or line
5 connections outside of the heart pacemaker housing.

In another embodiment, the sensor ~~could~~ can be implanted independently, remotely from the implanted medical device. Yet another alternative ~~would be~~ is to have the patient wear the sensor externally, such that the output signals from the sensor are transmitted by telemetry to the implanted medical device.

10 In any case, the sensor should be as small as possible, e.g. to allow incorporation into an implantable pacemaker, preferably 0.5 cm square, or less.

In a preferred embodiment the output signal is capacitance, which must first be converted to a voltage signal. The sensor response frequencies need to be calibrated to correspond with appropriate patient motion frequencies.

15 The use of a sensor of the present invention in combination with control circuitry for a heart pacemaker may be as follows (~~figure~~ Figure 2): The sensor 20 according to this embodiment of the invention ~~comprises~~ contains a fluid, whose properties of dielectric ~~permit-tivity~~ permittivity change when agitated, causing a corresponding change in the capacitance between two electrodes (as described
20 above). The variable capacitance is used as an input signal to ~~21. 21 is~~ an oscillator 21, which ~~yields~~ produces an output frequency that depends on the capacitance input. The frequency generated by the oscillator 21 is processed and converted to an appropriate signal in a 22 (~~frequency-to-activity-signal conversion~~) converter 22, as is known in the art. The signal from the converter 22 is combined
25 with input of a programmable target rate 31 ~~are~~ and is further processed in a 23 (~~reaction and recovery circuit~~) 23 to ensure appropriate reaction time and recovery time of the stimulation to the detected activity signals. ~~The remainder of the flow diagram 24 (pacemaker logic circuit) through 28~~ remaining components are standard and ~~is easily understood by the~~ known to those skilled person in the art

MARKED-UP COPY

of rate-responsive cardiac pacing. Those components include a pacemaker logic circuit 24, (25 refers to an output circuit 25, 26 to an ECG (electrocardiogram) filter and amplifier 26, 27 to a refractory unit 27, and 28 to a timer 28 for the highest inhibited rate). The total circuit is coupled to the heart 30 of a subject between the output circuit 25 and the ECG filter and amplifier 26. ~~The skilled person in the art would know the various components of the pacemaker circuit.~~ Reference is made to e.g. US-A-5233984 United States Patent No. 5,233,984 and to Lindgren and Jansson, "Heart Physiology and Stimulation, an introduction", 1992, Siemens-Elma AB, Solna, Sweden.

10 The control signal for the heart pacemaker may be generated in digital form instead of the analog format discussed above. Digital processing can be undertaken in a microprocessor. In both cases, the programming can be done via a telemetry ~~connection~~ link between the heart pacemaker and an external programming means.

15 In one embodiment of the invention a low/high frequency band pass filter (for measuring a patient's posture and activity) is used. This filter ~~should~~ preferably be is calibrated, since the fluid properties of the fluid of the sensor will affect sensor response frequencies. Filtering frequencies may therefore need adjustment.

20 Although modifications and changes may be suggested by those skilled in the art, it is the invention of the inventor to embody within the patent warranted heron all changes and modifications as reasonably and properly come within the scope of his contribution to the art.